



# **LEMI-030 Satellite Synchronized ULF Induction Magnetometer Set**

The complete set of magnetometer consists of three LEMI-30 sensors and one communication unit (CAM unit), which connects the sensors to PC and provides their power supply, satellite synchronization of data sampling and digitizing.

The induction magnetometer LEMI-30 is intended for the study of magnetic field fluctuations in the frequency band 0.001 ... 30 Hz in land conditions and is ideal for ULF earthquake precursors monitoring. It can be used both as a part of the computer measuring and registration equipment and autonomously with any analogue recorder. All three LEMI-30 sensors are similar within 0,1 dB.



**LEMI**

A KMS Technologies company

**Laboratory of ElectroMagnetic Innovation**



## Product Specifications

Frequency band of received signals	0.001 ... 30 Hz
Transformation coefficient value on 2 symmetrical output: on the flat part on the linear part where f frequency of received signal.	20 mV/nT; 200 mV/nT 20*f mV/nT; 200*f mV/nT
Transformation coefficient error	δ 3 dB
Noise rejection on (50 ± 0.2) or (60 ± 0.2) Hz	>60 dB
ADC (CAM unit) resolution	24 bit
GPS sampling synchronization and coordinates determination	
Power supply voltage	± (6 ... 12) V
Total power consumption	< 3 W
Temperature range of operation	minus 10 + 50°C
Outer dimensions	$l = 870 \text{ mm}; d = 85 \text{ mm}$
Weight of one sensor	5.6 kg
Waterproof housing	
Maximum length of connecting cable	200 m

Additional information at <http://lemisensors.com/?q=LEMI-030>

**LEMI**

A KMS Technologies company

6420 Richmond Ave., Suite 610

Houston, TX, 77057, USA

Tel.: +1.713.532.8144

Fax: +1.832.204.8418

[sales@lemisensors.com](mailto:sales@lemisensors.com)

[www.LEMIsensors.com](http://www.LEMIsensors.com)